

Azuero

NEW
NEU



available from 5/20
Verfügbar von 5/20

SAND FILTRATION SANDFILTER

NEW – INOVATIVE – DESIGN

NEUES – INOVATIVES – DESIGN

WaterStore.ua





TECHNICAL DATA TECHNISCHE DATEN

		AZURO 2m³ 3EXB0436	AZURO 4m³ + Timer 3EXB0437	AZURO 6m³ + Timer 3EXB0438
Voltage	Spannung	230 V / 50 Hz	230 V / 50 Hz	230 V / 50 Hz
Power consumption	Leistungsaufnahme	85 W	190 W	250 W
System flow-through	Systemdurchfluss	2 m³/h	4 m³/h	5.5 m³/h
Protection class	Schutzart	IP X5	IP X5	IP X5
Displacement	Verdrängung	1.5 m	1.5 m	1.5 m
Filter diameter	Filterdurchmesser	143 mm	143 mm	143 mm
Effective filtering surface	Wirksame Filterfläche	0.036 m²	0.036 m²	0.036 m²
For pools up to	Für Pools bis zu	8 m³	16 m³	30 m³
Turbidity reduction efficiency	Trübungsreduzierung	(TBR) 56%	(TBR) 56%	(TBR) 56%
Retained mass (DP20 test)	Einbehaltene Masse (DP20 test)	21 g	21 g	21 g
Operating pressure	Arbeitsdruck	0.2 bar	0.3 bar	0.5 bar
Maximum working pressure	Maximaler Arbeitsdruck	0.4 bar	0.6 bar	1.0 bar
Maximum water temperature	Maximale Wassertemperatur	35 °C	35 °C	35 °C
Sand capacity/type	Sandkapazität/typ	10 kg Quartz sand 0.6 - 1.2 mm	14 kg Quartz sand 0.6 - 1.2 mm	18 kg Quartz sand 0.6 - 1.2 mm
Connection	Anschluss	32/38 Pool hose, Poolschlauch	32/38 Pool hose, Poolschlauch	38 Pool hose, Poolschlauch

PACKAGE DETAIL VERPACKUNGSMASSE

